

**A METHOD FOR CONTRACTING, LOADING OR CRIMPING SELF-
EXPANDING AND BALLOON EXPANDABLE STENT DEVICES**

INS A1
ISS A2

BACKGROUND OF THE INVENTION

5 This invention relates to an apparatus and a method for reducing in size a medical device such as a stent, stent-graft, graft, or vena cava filter. The apparatus may be used in particular for fastening a medical device onto a catheter.

 Medical devices such as stents, stent-grafts, grafts, or vena cava filters and catheters for their delivery are utilized in a number of medical procedures and
10 situations, and as such their structure and function are well known.

 A stent, for example, is a generally cylindrical prosthesis introduced via a catheter into a lumen of a body vessel in a configuration having a generally reduced diameter and then expanded to the diameter of the vessel. In its expanded configuration, the stent supports and reinforces the vessel walls while maintaining the vessel in an
15 open, unobstructed condition.

 Stents are typically inflation expandable or self-expanding. Self expanding stents which are constrained by a sheath or other restraining means, must be provided in a reduced diameter.

 An example of a stent described in PCT Application No. 960 3092 A1,
20 published 8 February 1996.

 In advancing a stent through a body vessel to the deployment site, the stent must be able to securely maintain its axial position on the delivery catheter, without translocating proximally or distally, and especially without becoming separated from the catheter. Stents that are not properly secured or retained to the catheter may
25 slip and either be lost or be deployed in the wrong location. The stent must be crimped in such a way as to minimize or prevent altogether distortion of the stent and to thereby prevent abrasion and/or reduce trauma of the vessel walls.

 In the past, this crimping or size reduction has been done by hand often resulting in the application of undesired uneven forces to the stent. Such a stent must
30 either be discarded or re-crimped. Stents which have been crimped or otherwise reduced in size multiple times can suffer from fatigue and may be scored or otherwise marked which can cause thrombosis. A poorly crimped stent can also damage the underlying balloon.

EL813908635US

Recently, stent crimping devices have been disclosed in US 5,546,646 to Williams et al, US 5,183,085 to Timmermans et al., US 5,626,604 to Cottone, Jr., US 5,725,519, US 5,810,873 to Morales, WO 97/20593 and WO 98/19633.

A cam actuated stent crimper, shown in Figure 1, employs a plurality of
5 arc-shaped or curved slots with semi-circular ends, disposed such that each slot or cam engages a cam follower bearing 22. The arc-shaped or curved surfaces of the slots are inclined to be non-concentric relative to the axis of rotation 26, and therefore rotation of the cam plate 28 transmits equal radial displacements to the cam follower bearings 22, to simultaneously actuate a like number of linear bearings 24, which have their
10 corresponding linear tracks or rails mounted on a fixed plate. As shown in Fig.1 the cam plate rotary drive 29 comprises a pneumatic cylinder mounted on a pivot or trunnion, arranged with the cylinder rod connected rotatably to a short arm fixed rigidly to the cam plate. Accordingly, linear motion produced by the pneumatic cylinder translates into controllable arcs of motion of the circular cam plate, which has a
15 projecting V-shaped profile on its outer edge in rolling engagement with three equally spaced rollers with mating inverse V-shaped profiles to provide precise rotatable support to the cam plate. Depending on the direction of rotation, the linear slides which each carry a radially disposed crimping blade, are either moved inwards to apply a crimping force to the stent, or outwards to release the stent. Also when crimping,
20 depending on the degree of rotation of the cam plate, a specific radial crimping displacement may be obtained to match the diametral reduction required for any particular stent.

All US patents and applications and all other published documents mentioned anywhere in this application are incorporated herein by reference in their
25 entirety.

BRIEF SUMMARY OF THE INVENTION

It would be desirable to produce a device capable of crimping a stent uniformly while minimizing the distortion of and scoring and marking of the stent due
30 to the crimping. The present invention is directed to that end.

The present invention is particularly concerned with the crimping and otherwise reducing in size of inflation expandable stents, self-expanding stents and other expandable medical devices. For the purpose of this disclosure, it is understood

that the term 'stent' includes stents, stent-grafts, grafts and vena cava filters. It is also understood that the term 'crimping' refers to a reduction in size or profile of a stent.

In the description that follows it is understood that the invention contemplates crimping a medical device either directly to a catheter tube or to a catheter
5 balloon which is disposed about a catheter tube. When reference is made to crimping a medical device to a catheter, a balloon may be situated between the medical device and the catheter tube or the medical device may be crimped to a region of a catheter tube directly. The invention also contemplates crimping a stent in the absence of a catheter to reduce the stent in size.

10 The present invention is directed, in one embodiment, to an apparatus for reducing a medical device in size. Desirably, the medical device is a stent, a stent-graft, a graft or a vena cava filter, whether self-expandable, balloon expandable or otherwise expandable, although the inventive apparatus may also be employed with any other suitable, generally tubular medical device which must be reduced in size.

15 The inventive apparatus comprises at least three coupled movable blades disposed about a reference circle to form an aperture whose size may be varied. Each blade is in communication with an actuation device which is capable of moving the blade to alter the size of the aperture. Each blade includes a single radial point on the surface of the blade which a) lies on the circumference of the reference circle prior to
20 movement of the blade, and b) may be moved only along a radius of the reference circle on movement of the blade.

The apparatus further includes an actuation device which comprises a cam and a plurality of linear slide devices. Each linear slide device is in communication with a blade. Each of the linear slide devices is also in mechanical communication with
25 the cam. Rotation of the cam results in linear translation of the slide device and blade, such that the slide device moves along an axis parallel to the radius on which the radial point of the blade lies or along the radius itself.

The invention is also directed to an apparatus similar to that described above, with blades disposed about a reference tube to form a tubular aperture whose size
30 may be varied. Each blade is in communication with an actuation device which is capable of moving the blade to alter the size of the tubular aperture. Each blade includes a single line which a) lies on the surface of the reference tube prior to

movement of the blade, and b) may be moved only along a radial plane of the reference tube on movement of the blade.

The inventive apparatus finds particular utility in crimping a medical device such as those mentioned above to a catheter or to a balloon disposed about a catheter.

The inventive apparatus also finds utility in reducing the diameter of a medical device such as those mentioned above prior to crimping.

The invention is also directed to a method of manipulating a medical device which comprises the steps of providing the medical device and providing at least three blades capable of applying a radial inward force. The blades are disposed about a reference circle to form a shrinkable aperture. A medical device such as a stent is placed into the shrinkable aperture and the blades simultaneously moved inward to apply a radial inward force to the medical device. The blades are constructed and arranged such that each blade has a single point which a) lies on the circumference of the reference circle prior to movement of the blade, and b) is moved along a radius of the reference circle on movement of the blade.

The inventive apparatus may also be used as a variable size balloon mold. To that end, the invention is further directed to a method of molding a medical balloon. In the practice of the method, a balloon preform prepared through any suitable technique known in the art is provided. The preform is placed in an apparatus which has a shrinkable tubular aperture formed by at least three movable blades disposed about a reference tube. The blades are constructed and arranged such that each blade has a single line which a) lies on the surface of the reference tube prior to movement of the blade, and b) is moved along a radial plane of the reference tube on movement of the blade. The aperture may be set to a predetermined size prior to placement of the preform therein or after placement of the preform therein. An inflation fluid is supplied to the balloon preform to expand the balloon preform until it contacts the blades. The preform may optionally be heated prior to, during or after the blowing step. The thus formed balloon is then pressure relieved and removed from the apparatus.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

Figure 1 shows a perspective view of a stent crimper;

Figure 2a is a schematic front view of an embodiment of the inventive apparatus;

Figure 2b is a schematic front view of the embodiment of Fig. 2a after the stent has been reduced in size;

5 Figures 3a and 3b are schematics of blades;

Figure 3c is a partial schematic front view of an embodiment of the inventive apparatus employing the curved blades of Figure 3b;

Figure 4a is a partial front view of an embodiment of the inventive apparatus;

10 Figure 4b is a partial front view of an embodiment of the inventive apparatus;

Figure 4c shows a side view of the embodiment of Figure 4b taken along lines 4c-4c;

15 Figure 5a shows a partial front view of another embodiment of the inventive apparatus;

Figure 5b shows a link connected to a blade;

Figure 6 is a schematic, perspective view of an embodiment of the inventive apparatus;

Figure 7 shows a partial view of the embodiment of Figure 6;

20 Figures 8a and 8b are partial side elevational views of an embodiment of the inventive apparatus taken along a radial plane during the size reduction process;

Figure 8c is a partial side elevational view of an embodiment of the inventive apparatus taken along a radial plane following crimping of a stent to a catheter;

25 Figure 9 is a diagrammatic side elevational view of an embodiment of the inventive apparatus;

Figure 10 is a partial side elevational view of an embodiment of the inventive apparatus taken along a radial plane of an embodiment of the invention consisting of three individual apparatuses arranged sequentially;

30 Figure 11 is a schematic showing a stent being reduced in size and loaded into a sheath;

Figure 12 is a partial side elevational view of an embodiment of the inventive apparatus taken along a radial plane showing a balloon that has been molded with the inventive device; and

Figure 13 is a partial side elevational view taken along a radial plane
5 showing a stepped balloon that has been molded with the inventive device.

DETAILED DESCRIPTION OF THE INVENTION

While this invention may be embodied in many different forms, there are described in detail herein specific preferred embodiments of the invention. This
10 description is an exemplification of the principles of the invention and is not intended to limit the invention to the particular embodiments illustrated.

As shown generally at 100 in Figures 2a and 2b, the inventive apparatus comprises eight coupled blades 106 disposed about a reference circle 114 to form an aperture 118 whose size may be varied. The apparatus may comprise as few as three
15 blades and as many as sixteen or more blades. Desirably, the apparatus will have four or more blades and more desirably, eight or more blades. The maximum number of blades is limited only by how many blades can physically be coupled together under the relevant size constraints. As the number of blades is increased, the profile of the aperture and hence of the medical device following reduction in size, becomes
20 smoother. Figure 2b shows the apparatus of Figure 2a after the stent has been reduced in size.

Blades 106 as shown in Figure 3a have an inner end 108 which is desirably beveled 111 so as to mesh with adjacent blades and an outer end 110 which is displaced from aperture 118. Aperture 118 is polygonal. Blades 106 may also be shaped
25 with a curved end 112, as shown in Figures 3b and 3c so as to form a substantially circular shaped aperture, when the aperture is fully closed.

Each blade 106 includes a single radial point 122 which lies on a radial line 126 of reference circle 114 prior to movement of blade 106 and which may be moved only along the radius 126 of reference circle 114 on movement of blade 106.
30 Desirably, the single radial point 122 will be disposed at the tip of the blade adjacent to beveled end 111.

In the embodiment shown in Figure 4a, radial point 122 lies at the tip of blade 106. Each blade 106 has a connecting link 130 extending from second end 110.

Connecting link 130 ends in mounting means 134, typically a mounting flange adapted for attachment to a linear bearing block, for interfacing with an actuation device, shown generally at 138. Actuation device 138 is capable of simultaneously moving blades 106 to alter the size of aperture 118.

5 Actuation device 138 includes actuation plate 142 which is coaxial with reference circle 114. Actuation plate 142 has eight equi-spaced radial slots 146. More generally, for every blade there will be a corresponding radial slot on actuation plate 142. Each radial slot 146 overlaps a mounting means 134 for a linear bearing block at the end of a connecting link 130. Each blade 106 is engaged to actuation plate 142 via a
10 cam follower bearing 150 disposed in radial slot 146 and attached to mounting means in slotted end 134.

Each bearing 150 extends from a linear slide 154. Linear slide 154 is mounted on a non-rotating plate 156 (shown in Figure 8). Linear slide 154 is constructed and arranged to slide along a line 158 which is parallel to the radius 126 on
15 which radial point 122 of blade 106 lies.

For the purposes of this disclosure, the term 'cam follower bearing' includes cam follower bearings, low friction rollers, roller bearings, needle roller bearings and a slipper block pivot mounted on a bearing and stub shaft. Figure 4b is a partial front view of an embodiment in which a slipper block is used. A side view of the
20 embodiment of Figure 4b taken along lines 4c-4c is shown in Figure 4c. Slipper block 150 resides in slot 146 of actuation plate 142. Slipper block 150 is mounted on stub shaft 151 which extends from connecting link 130. Desirably, bearings 153 will be present between shaft 151 and slipper block 150. Connecting link 130, in turn, is fastened to linear bearing block 212 via fasteners 214. Bearing block 212 is linearly
25 mounted on linear slide which is mounted on fixed plate 156. Linear motion is facilitated by the presence of bearings 216.

Cam follower bearing 150 may be replaced by any other suitable connecting member which can connect the slide and the link.

In use, as actuation plate 142 is rotated in a clockwise direction, the
30 clockwise motion of the actuation plate is translated into linear motion of each of linear slide 154 and blade 106 via bearing 150. Each blade 106 moves outward in a direction parallel to the radius 126 on which the radial point 122 of the blade 106 lies, resulting in the opening of aperture 118. As actuation plate 142 is rotated in a counterclockwise

direction, each blade 106 moves inward in a direction parallel to the radius 126 on which the radial point 122 of the blade 106 lies, resulting in the closing of aperture 118. As aperture 118 closes, a radially inward force is applied to a medical device disposed in the aperture. The actuation plate is rotated until the desired size reduction of the aperture and medical device has been achieved. Following the reduction, the actuation plate is rotated in the opposite direction to allow for removal of the medical device from the aperture.

The apparatus may be used to reduce the diameter of a suitable medical device such as those disclosed above or may be used to crimp a medical device to a catheter.

Another embodiment of the invention is shown in Figure 5a. Each blade 106, as shown in Figure 5a, has a connecting link 130 extending therefrom. Connecting link 130 is rigidly attached to blade 106. Connecting link 130 ends in an angled end 134 for interfacing with an actuation device, shown generally at 138. Actuation device 138 is capable of simultaneously moving blades 106 to alter the size of aperture 118.

INS A-3 Actuation device 138 includes a rotatable actuation plate 142 which is co-axial with reference circle 114. Rotatable actuation plate includes cam slots 146 which are not concentric with the axis of rotation, arcing inward. Each connecting link 130 is engaged to actuation plate 146 via a cam follower bearing 150 disposed in slot 146 and attached to both angled end 134 of connecting link 130 and to a linear slide 154. Linear slide 154 is mounted on a non-rotating plate similar to that shown in Figure 8. Linear slide 154 is constructed and arranged to slide along a radial line 158 on which radial point 122 of blade 106 lies.

Connecting link 130 may be bonded adhesively, welded, joined with a fastener or otherwise joined to blade 106. As shown in Figure 5a, a single screw 131 is used to connect link 130 to blade 106. Figure 5b shows a connecting link 130 including a right angle portion which is fastened to a blade 106 using two screws 131. Connecting link 130 and blade 106 may optionally be formed of a single piece of material. Regardless of how the connecting member is joined to the blade, no movement of the blade relative to the connecting link is permitted.

In use, as actuation plate 142 is rotated in a clockwise direction, the clockwise motion of the actuation plate is translated into a linear outward motion of each of linear slides 154 and blades 106 via bearings 150 resulting in the opening of

aperture 118. The outward motion results from the radially outward arcing of cam slot 146. As actuation plate 142 is rotated in a counterclockwise direction, each blade 106, because of the radially inward arc of cam slots 146, moves inward in a direction parallel to the radius 126 on which the radial point 122 of the blade 106 lies, resulting in the
5 closing of aperture 118. As discussed above, as the aperture is decreased in size, a radial inward force is brought to bear against a medical device disposed in the aperture, thereby reducing the size of the medical device.

The embodiment of Figure 5a differs from the embodiment of Figure 4a in that in the embodiment of Figure 5a, the slide moves along the radial line on which
10 the radial point of the attached blade lies whereas in Figure 4a the slide moves parallel to the radial line. In both of the embodiments, each of the blades is constrained with two degrees of freedom to satisfy the condition that the movement of the tip be radial in accordance with the invention.

In the embodiments of Figures 4a and 5a, the slots in the actuation plate
15 are constructed and arranged to allow for a sufficient reduction in size of the aperture so that a medical device can be reduced in size to a desired diameter. Those of ordinary skill in the art will recognize other suitable actuation devices that may be used in the practice of this invention.

Desirably, in the above embodiments, the blades will be as long as or
20 longer than the medical device disposed within so that the medical device is uniformly reduced in size along its entire length.

This is illustrated in the embodiment of Figures 6 and 7 and further in Figures 3a and 3b in which blades 106 are disposed about a reference tube 160 to form a tubular aperture 162 whose size may be varied. Reference circle 114 is seen to lie along
25 reference tube 160. Each blade 106 is in communication with an actuation device such as that shown in Figures 4 or 5. The actuation device is capable of moving blades 106 to alter the size of tubular aperture 162. Each blade 106 includes a single line 166 which a) lies on a radial plane 170 of the reference tube 160 prior to movement of blade 106, and b) may be moved only along a radial plane 170 of reference tube 160 on
30 movement of blade 106. Desirably, reference tube 160 is cylindrical and exceeds the length of the medical device to be reduced in size.

Another embodiment of the invention is illustrated in Figures 8a and 8b. In the embodiment of Figures 8a and 8b, two non-rotating plates 156 are present, one at

each end of the apparatus. Each blade 106 is connected at first end 174 to a linear slide 154a via a connecting link 130a and at second end 178 to a linear slide 154b via a connecting link 130b. Linear slide 154a is mounted on non-rotating plate 156a and linear slide 154b is mounted on non-rotating plate 156b. The presence of the second
5 non-rotating plate 156b, linear slide 154b and connecting link 130b is optional but contributes to providing a rigid frame upon which the connecting links and associated blades may slide without misalignment relative to the reference circle.

Figures 8a and 8b illustrate the use of the inventive apparatus in various stages of the size reduction process. In Figure 8a, stent 180 has been placed in tubular
10 aperture 162 which is characterized by a diameter d_1 . In Figure 8b, the device has been actuated by rotating actuation plate 142 so as to move blades 106 inward. Aperture 162, as shown in Figure 8b is characterized by a diameter d_2 which is reduced relative to diameter d_1 . Stent 180 is seen to be of reduced diameter relative to its previous diameter as shown in Figure 8a.

15 Figure 8c differs from Figure 8b, only in that stent 180 has been crimped onto catheter 184 in Figure 8c.

Blades 106 may be made of any suitable, hard material including hardened steel. Desirably, the blades will be made of a material such as zirconia ceramic. Blades made of zirconia ceramic may be used without lubrication.
20 Furthermore, because of their low thermal conductivity, they may be used to create a highly insulated chamber suitable for cryogenic processing of martensite in nitinol stents.

Such an embodiment is shown in Figure 9. Stent 180 is disposed between blades 106 which can move inward in the direction of the arrows. Blades 106
25 are cooled by a first source of cooling fluid 184 located at first end 174 of blades 106. Although not shown, a second source of cooling fluid may be provided at second end 178 of blades 106 as well. The cooling fluid may be a liquid cryogenic. Exemplary cryogenics include liquid nitrogen, argon or carbon dioxide although other cryogenics may also be used. The cooling fluid may also be a chilled gas such as air. The cooling
30 fluid may also be a cooled inert gas such as nitrogen, argon or other inert gasses.

The aperture formed by the blades is a highly insulated chamber which is suitable for cryogenic processing of martensite in nitinol stents. The chamber is maintained at -80°C and a nitinol stent inserted therein. Upon equilibration of the

temperature of the stent, the blades are moved inward to reduce the diameter of the stent. The stent is thus reduced in diameter while being maintained in the martensitic state.

The embodiment of Figure 9 further has a loading plunger 188 for
5 loading a stent or other suitable medical device into the aperture. A sheath housing 192 which houses sheath 196 is provided at second end 178 of blades 106. Plunger 188 may be further used to transfer the stent after it has been reduced in diameter or size to sheath 196. Desirably, sheath 196 will have a slightly larger diameter than stent 180 following reduction in size of the stent. More desirably, the fit of the stent within the sheath will
10 be within about 1/32" and even more desirably, within about 1/64".

Where lengthy stents or other medical devices are to be reduced in size, the invention contemplates using one of the above described apparatuses with long blades to accommodate the stent. As an alternative, the invention also contemplates disposing two or more of such apparatuses sequentially to form one long aperture. The
15 two or more apertures may then be reduced in size simultaneously or consecutively. The arrangement of Figure 10 shows an embodiment with three devices 100a-c arranged sequentially. A stepped reduction in size may be achieved by placing a stent 180 or similar medical device in the apparatus and independently reducing each aperture 118 a-c to a desired size. To that end, the invention may provide particular utility in
20 manipulating bifurcated stents or other stents whose diameter varies along its length. The embodiment of Figure 10 shows the end portions of the stent being reduced in size prior to the middle portion of the stent. The device may also be operated so as to reduce the middle portion in size prior to the end portions or in any other sequence.

The invention contemplates yet another approach to reducing the
25 diameter of lengthy stents or similar medical devices, namely walking the stent through the apparatus. This may be accomplished by either moving the stent relative to the apparatus or moving the apparatus relative to the stent as shown schematically in Figure 11. To that end, stent 180 is inserted in device 100. Aperture 118a is reduced in size with blades 106a in turn reducing portion 180a of stent 180 in size. Aperture 118a is
30 then opened and aperture 118b reduced in size thereby reducing portion 180b of stent 180. Simultaneously, or shortly thereafter, sheath 196 is pushed by plunger 188 over the portion of the stent that has been reduced in size. Aperture 118b is opened and the stent

advanced in the apparatus. The process is repeated until the entire length, or the desired portion of the stent or medical device is reduced in size.

The reduction in size of the stent or other medical device may occur as part of a precrimping step or it may occur as part of crimping a stent onto a catheter and desirably, onto a balloon disposed about a catheter. In a general sense, it may be used for manipulating a medical device and specifically, for applying a radial inward force to a medical device.

In another embodiment, the invention is directed to a method of manipulating a medical device. As part of the method, a medical device such as those disclosed above is provided. The device has at least three blades capable of applying a radial inward force. The blades are disposed about a reference circle to form a shrinkable aperture. The blades are constructed and arranged such that each blade has only a single point which a) lies on the circumference of the reference circle prior to movement of the blade, and b) is moved along a radius of the reference circle on movement of the blade. The medical device is placed into the shrinkable aperture and the blades simultaneously moved inward to apply a radial inward force to the medical device and thereby reduce the medical device in size, and desirably, in diameter. Following reduction in size of the medical device, the blades are simultaneously moved outward and the medical device removed from the aperture.

The inventive apparatus may also be incorporated into a blow molding tool to provide a variable size balloon mold as shown generally at 100 in Figure 12. The various parts of the apparatus of Figure 12 have been discussed in conjunction with Figures 8a-c and, with exception of balloon 181 and mold cavity ends 193, the reference numerals used in Figure 12 correspond to those used for Figures 8a-c. Mold cavity ends 193 may be provided in a variety of sizes and lengths to contain the balloon at each end. Desirably, the end molds will be adjustably mounted to a portion of the apparatus such as fixed plates 156 to provide for an adjustable length balloon mold.

The invention is also directed to a method for molding a medical balloon using the inventive apparatus described above. A balloon preform prepared through any standard method is provided. The inventive mold, shown generally at 100 is also provided. Balloon 181 is inserted into aperture 162. Aperture 162 is optionally reduced to a predetermined size and the preform expanded using standard techniques. An

inflation fluid, for example, may be supplied to the preform and the preform expanded and heated. The balloon in its expanded state is shown in Figures 12.

More generally, the invention may be practiced by providing at least three movable blades disposed about a reference tube to form a shrinkable tubular
5 aperture. The blades are constructed and arranged such that each blade has a single line which a) lies on the surface of the reference tube prior to movement of the blade, and b) is moved along a radial plane of the reference tube on movement of the blade. A balloon preform is placed into the shrinkable aperture. The aperture may be set at a predetermined size prior to or following insertion of the balloon therein. An inflation
10 fluid is provided and the balloon preform inflated so that the preform expands to the size of the aperture. The preform may be heated during this inflation/blowing step. The inflation fluid is then removed from the thus formed balloon and the balloon removed from the apparatus.

The balloon may be also be molded in accordance with the method
15 described in US 5,163,989, or in accordance with other methods as are known to those of ordinary skill in the art, substituting the instant apparatus for the standard balloon mold. Other patents which discuss balloon molding include US 5,807,520. Other references illustrating the materials and methods of making catheter balloons include: US 4,413,989 and US 4,456,000 to Schjeldahl et al, US 4,490,421, US Re 32,983 and
20 Re 33,561 to Levy, and US 4,906,244, US 5,108,415 and US 5,156,612 to Pinchuck et al.

The use of the inventive apparatus as a mold allows for the blowing of a balloon to a predetermined size using a single adjustable size balloon mold thereby eliminating the need to have multiple molds of different sizes.

25 The invention further contemplates molding a balloon to a desired shape using a plurality of the inventive devices arranged sequentially. As an example of this, shown in Figure 13, a stepped balloon 181 may be prepared by arranging several devices 100a, 100b and 100c sequentially. A balloon preform is inserted in the aperture formed by the device. The aperture of each device may be preset at a desired size or may be
30 reduced in size to a predetermined size after the balloon preform is inserted therein. The balloon may then be blow molded in accordance with any suitable blow molding technique known in the art.

The invention is also understood to be directed to embodiments employing various combinations of the features disclosed herein.

The above disclosure is intended to be illustrative and not exhaustive. This description will suggest many variations and alternatives to one of ordinary skill in
5 this art. All these alternatives and variations are intended to be included within the scope of the attached claims. Those familiar with the art may recognize other equivalents to the specific embodiments described herein which equivalents are also intended to be encompassed by the claims attached hereto.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000